

greasing equipment - hand operated

minilube®

K7

A portable greasing system designed for use on-site or in workshop environments. Macnaught produces models to suit pail sizes from 2.5 kg (5 lbs) to 5 kg (11 lbs) with depths of 146 mm to 225 mm.

Features

- spring loaded system - 30 shots of grease per prime
- high pressure, high volume KR grease gun
- 1.5 m (5 ft) x 12 mm (1/2") ID delivery hose
- rubber edged follower
- 360° swivel to prevent hose kinking
- fully sealed to prevent contamination
- complete set with refillable containers K6-24 (2.5 kg, 5 lbs) or K6-67 (5 kg, 11 lbs) available
- refillable containers also available separately (KT5, KT6)
- fully serviceable
- 10 year warranty and parts guarantee

Specifications

- grease viscosity:
up to NLGI No.2
- wetted components:
aluminium, steel, brass and nitrile rubber
- gun pressure:
up to 69 000 kPa (10 000 psi, 690 bar) on high pressure
- output:
approx. 1.25 g on the high volume setting
approx. 0.45 g on the high pressure setting

Accessories

- KT5 (2.5 kg)/KT6 (5 kg) Grease Container
- KZD Needlenose Coupler
- KZHY Hyperdermic Needlepoint Coupler
- KFR Rigid/Flexible Extension
- KDF13 Flexible Extension
- KSR Standard Buttonhead Coupler

