

oil transfer equipment - hand operated

multi purpose pump

A2 (pump only)
A2H (pump with hose)

A classic Macnaught hand pump, the A2 and A2H is ideal for transferring a wide range of mineral oils and non-corrosive solvents and chemicals.

Features

- telescopic suction tube fits 60 L (16 US gal) to 205 L (55 US gal) drums
- A2H supplied with 1.8 m (6 ft) delivery hose and nozzle
- Nitrile, viton and EPDM o-rings supplied (Nitrile fitted as standard)
- variable handle setting for light or heavy fluids
- built-in bung opener
- fully serviceable
- 10 year warranty and parts guarantee

Specifications

- compatible fluids: diesel, lubricating oils up to SAE 90 and other non - corrosive solvents and chemicals. Chemical compatibility chart supplied. To determine compatibility with liquids not listed, check with liquid supplier and quote wetted components listed below.
- wetted components: aluminium, steel, brass, Teflon and either Nitrile, Viton or EPDM depending on o-ring
- output: approx. 250 mL per stroke (4 strokes per L)



A2H

macnaughtdesign
10 year warranty

oil pump

C65P

A low cost oil pump suitable for 20 litre containers

Features

- built in oil drain back facility
- 1.5 m anti-kink hose
- non-drip dispensing nozzle

Specifications

- delivers approximately 65 mL (14 strokes per litre) on the down stroke
- suitable for oils and non-corrosive liquids up to SAE140



C65P